

Claims

1
2 1. Regulated dashpot with shock-absorption force controls,
3 especially intended for motor vehicles, with at least one flow-
4 regulating system including one or more shock-absorption
5 components for the compression phase and/or for the decompression
6 phase, characterized in that at least one valve assembly is
7 supplied with variable flow impedance by a regulating valve (5,
8 6, 26, or 31).

9
10 2. Dashpot as in Claim 1, characterized by at least one
11 fixed bypass valve (7, 19, 20, or 33) with a constricted cross-
12 section hydraulically paralleling the flow-regulating systems.

13
14 3. Dashpot as in Claim 1 or 2, characterized by at least one
15 flow regulating system for the compression phase and at least one
16 for the decompression phase in the form of regulating valves (5 &
17 6) with a variable flow constriction.

18
19 4. Dashpot as in one or more of Claims 1 through 3,
20 characterized by previously adjusted pressure-dependent valve
21 assemblies (18) with a fixed flow cross-section for the
22 compression and/or decompression phase and with a hard
23 performance curve, hydraulically paralleling the flow-regulating
24 and/or shock absorption systems.

25
26 5. Dashpot as in one or more of Claims 1 through 4,
27 characterized by previously adjusted pressure-dependent valve

1 assemblies (18) with a fixed flow cross-section for the
2 compression and/or decompression phase and with a soft
3 performance curve, that can be activated and deactivated
4 individually or separately, hydraulically paralleling the flow-
5 regulating and/or shock absorption systems.

6
7 6. Dashpot as in one or more of Claims 1 through 5,
8 characterized in that the flow-regulating, flow-constricting, or
9 shock-absorption systems are accommodated in a separate
10 component, preferably in the form of a flow regulating block (41)
11 outside the dashpot and communicating with it by way of
12 hydraulic-fluid lines.

13
14 7. Dashpot as in one or more of Claims 1 through 5,
15 characterized in that the flow-regulating, flow-constricting, or
16 shock-absorption systems are accommodated in or on its piston
17 (3).

18
19 8. Dashpot as in one or more of Claims 1 through 5,
20 characterized in that the flow-regulating, flow-constricting, or
21 shock-absorption systems are accommodated in or on its bottom
22 valve (46).

23

24

25

26

27